

Please provide the following information, and submit to the NOAA DM Plan Repository.

Reference to Master DM Plan (if applicable)

As stated in Section IV, Requirement 1.3, DM Plans may be hierarchical. If this DM Plan inherits provisions from a higher-level DM Plan already submitted to the Repository, then this more-specific Plan only needs to provide information that differs from what was provided in the Master DM Plan.

URL of higher-level DM Plan (if any) as submitted to DM Plan Repository:

1. General Description of Data to be Managed**1.1. Name of the Data, data collection Project, or data-producing Program:**

2013 USACE Topobathy Lidar: Stamp Sands, Lake Superior (MI)

1.2. Summary description of the data:

These files contain classified topographic and bathymetric lidar data as unclassified valid topographic data (1), and valid topographic data classified as ground (2), Classes 1 and 2 are defined in accordance with the American Society for Photogrammetry and Remote Sensing (ASPRS) classification standards. These data were collected by the Coastal Zone Mapping and Imaging Lidar (CZMIL) system. Class 29 Bathymetric points were converted to class 11 to fit the OCM scheme for bathy points. CZMIL integrates a lidar sensor with topographic and bathymetric capabilities, a digital camera and a hyperspectral imagery on a single remote sensing platform for use in coastal mapping and charting activities. Native lidar data is not generally in a format accessible to most Geographic Information Systems (GIS). Specialized in-house and commercial software packages are used to process the native lidar data into 3-dimensional positions that can be imported into GIS software for visualization and further analysis. Horizontal positions, provided in decimal degrees of latitude and longitude, are referenced to the North American Datum of 1983 National Adjustment of 2011 (NAD83 NA2011). Vertical positions are referenced to the NAD83 NA11 ellipsoid and provided in meters. The National Geodetic Survey's (NGS) GEOID12A model is used to transform the vertical positions from ellipsoid to orthometric heights referenced to the North American Vertical Datum of 1988 (NAVD88). Once converted to orthometric heights, the data are then converted to the International Great Lakes Datum of 1985 (IGLD85) using the VDatum program from NOAA (National Oceanic and Atmospheric Administration). The 3-D position data are sub-divided into a series of LAS files, which are tiled into quarter-quads or 5km boxes. The LAS file index is provided by the shape file, "mi_superior_boxes.shp", and the numbers used to identify files are in the "Box" field of the shape file. The data file naming convention is based on the year, effort, area name, "Box" number and product type. An example file name is "2013_NCMP_MI_Superior_01_GeoClassified", where 2013 is the year of data collection, NCMP is the project under which data were collected, MI_Superior is the area of data collection, 01 is the "Box" number and GeoClassified is the product type. Digital

Elevation Models(DEMs) created from this data are available. The bare earth DEMs are at a 1 meter grid size. These products have not been reviewed by the NOAA Office for Coastal Management and any conclusions drawn from the analysis of this information are not the responsibility of NOAA or the Office of Coastal Management (OCM). The data are available upon request via email at: coastal.info@noaa.gov. Please provide the name of the data set and "DEM Request" in the subject line, though we do not have the hyperspectral imagery that was acquired during the same missions; for these please reach out to JALBCTX@usace.army.mil.

1.3. Is this a one-time data collection, or an ongoing series of measurements?

One-time data collection

1.4. Actual or planned temporal coverage of the data:

2013-07-11

1.5. Actual or planned geographic coverage of the data:

W: -88.2672039, E: -88.0937302, N: 47.2740777, S: 47.141536

1.6. Type(s) of data:

(e.g., digital numeric data, imagery, photographs, video, audio, database, tabular data, etc.)
las

1.7. Data collection method(s):

(e.g., satellite, airplane, unmanned aerial system, radar, weather station, moored buoy, research vessel, autonomous underwater vehicle, animal tagging, manual surveys, enforcement activities, numerical model, etc.)

1.8. If data are from a NOAA Observing System of Record, indicate name of system:

1.8.1. If data are from another observing system, please specify:

2. Point of Contact for this Data Management Plan (author or maintainer)

2.1. Name:

NOAA Office for Coastal Management (NOAA/OCM)

2.2. Title:

Metadata Contact

2.3. Affiliation or facility:

NOAA Office for Coastal Management (NOAA/OCM)

2.4. E-mail address:

coastal.info@noaa.gov

2.5. Phone number:

(843) 740-1202

3. Responsible Party for Data Management

Program Managers, or their designee, shall be responsible for assuring the proper management of the data produced by their Program. Please indicate the responsible party below.

3.1. Name:

3.2. Title:

Data Steward

4. Resources

Programs must identify resources within their own budget for managing the data they produce.

4.1. Have resources for management of these data been identified?

4.2. Approximate percentage of the budget for these data devoted to data management (specify percentage or "unknown"):

5. Data Lineage and Quality

NOAA has issued Information Quality Guidelines for ensuring and maximizing the quality, objectivity, utility, and integrity of information which it disseminates.

5.1. Processing workflow of the data from collection or acquisition to making it publicly accessible

(describe or provide URL of description):

Process Steps:

- 2013-07-11 00:00:00 - These data were collected using the CZMIL system. It is owned and operated by the U.S. Army Corps of Engineers (USACE). The system collects lidar data at 20 kHz and RGB imagery at 2 Hz. A CASI-1500 hyperspectral line scanner is integrated with the system as well. Aircraft position, velocity and acceleration information are collected through a combination of Novatel and POS A/V 510 equipment. All raw data streams are transferred to the office for downloading and processing in CZMILs Hydro Fusion software. Aircraft position data are processed using POSpac software and the results are combined with the lidar data to produce 3-D positions for each lidar shot. Upon inspection and QA/QC in the software packages Fledermaus and PFM_ABE, anomalous data are flagged as invalid. NOAA's VDatum software then converts all valid data from ellipsoid to orthometric heights based on the NGS' GEOID12A model and exports valid lidar data as a series of unclassified ascii xyz files.
- 2014-01-22 00:00:00 - ASCII files are imported into GeoCue V2012.1.27.7, which is a geospatial workflow production and management software tool employed by JALBTCX to perform and monitor production of data products. Upon import into GeoCue, the ASCII files are converted to LAS format. A customized classification macro, built upon the TerraScan V13 module within Microstation V8i, classifies

valid topographic data as ground points (2) and unclassified points (1). Upon completion the macro, the classification results undergo quality control and any misclassified points are manually edited. In areas of dense vegetation the bare earth ground points might be incorrectly classified due to the inability of the laser to penetrate the canopy and reach the bare ground. In these areas, JALBTCX defaults to the algorithms ground surface instead of manually reclassifying those points. The final classification results are comprised of individual lidar points with classifications of ground (2) or unclassified (1). They are partitioned into a series of 5km or quarter quad delivery boxes, one Classified LAS file per box. The format of the file is LAS version 1.2. Data are classified as 1 (valid non-ground topographic data), 2 (valid ground topographic data), 21 (valid topographic data acquired with the bathymetric sensor), 27 (invalid topographic and bathymetric data), 29 (valid bathymetric data).

- 2014-07-15 00:00:00 - The NOAA Office for Coastal Management (OCM) received the topographic/bathymetric files in LAS format from USACE. The files contained lidar easting, northing, elevation, intensity, return number, etc. The data was received in Geographic Coordinates (decimal degrees). The vertical coordinates were referenced to IGLD85 in meters using the Geoid12a model. OCM performed the following processing for data storage and Digital Coast provisioning purposes: 1. Class 29 points (bathymetry) were reclassified to Class 11 (bathymetry) to fit OCM DAV class scheme. 2. LAS files were converted to NAVD88 orthometric heights then to ellipsoidal vertical coordinates.

5.1.1. If data at different stages of the workflow, or products derived from these data, are subject to a separate data management plan, provide reference to other plan:

5.2. Quality control procedures employed (describe or provide URL of description):

6. Data Documentation

The EDMC Data Documentation Procedural Directive requires that NOAA data be well documented, specifies the use of ISO 19115 and related standards for documentation of new data, and provides links to resources and tools for metadata creation and validation.

6.1. Does metadata comply with EDMC Data Documentation directive?

No

6.1.1. If metadata are non-existent or non-compliant, please explain:

Missing/invalid information:

- 1.7. Data collection method(s)
- 3.1. Responsible Party for Data Management
- 4.1. Have resources for management of these data been identified?
- 4.2. Approximate percentage of the budget for these data devoted to data management

- 5.2. Quality control procedures employed
- 7.1. Do these data comply with the Data Access directive?
 - 7.1.1. If data are not available or has limitations, has a Waiver been filed?
 - 7.1.2. If there are limitations to data access, describe how data are protected
- 7.4. Approximate delay between data collection and dissemination
- 8.1. Actual or planned long-term data archive location
- 8.3. Approximate delay between data collection and submission to an archive facility
- 8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

6.2. Name of organization or facility providing metadata hosting:

NMFS Office of Science and Technology

6.2.1. If service is needed for metadata hosting, please indicate:**6.3. URL of metadata folder or data catalog, if known:**

<https://www.fisheries.noaa.gov/inport/item/49809>

6.4. Process for producing and maintaining metadata

(describe or provide URL of description):

Metadata produced and maintained in accordance with the NOAA Data Documentation Procedural Directive: https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC_PD-Data_Documentation_v1.pdf

7. Data Access

NAO 212-15 states that access to environmental data may only be restricted when distribution is explicitly limited by law, regulation, policy (such as those applicable to personally identifiable information or protected critical infrastructure information or proprietary trade information) or by security requirements. The EDMC Data Access Procedural Directive contains specific guidance, recommends the use of open-standard, interoperable, non-proprietary web services, provides information about resources and tools to enable data access, and includes a Waiver to be submitted to justify any approach other than full, unrestricted public access.

7.1. Do these data comply with the Data Access directive?

7.1.1. If the data are not to be made available to the public at all, or with limitations, has a Waiver (Appendix A of Data Access directive) been filed?

7.1.2. If there are limitations to public data access, describe how data are protected from unauthorized access or disclosure:

7.2. Name of organization of facility providing data access:

NOAA Office for Coastal Management (NOAA/OCM)

7.2.1. If data hosting service is needed, please indicate:**7.2.2. URL of data access service, if known:**

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=3670>

https://coast.noaa.gov/htdata/lidar4_z/geoid18/data/3670

7.3. Data access methods or services offered:

This data can be obtained on-line at the following URL:

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=3670>;

7.4. Approximate delay between data collection and dissemination:**7.4.1. If delay is longer than latency of automated processing, indicate under what authority data access is delayed:****8. Data Preservation and Protection**

The NOAA Procedure for Scientific Records Appraisal and Archive Approval describes how to identify, appraise and decide what scientific records are to be preserved in a NOAA archive.

8.1. Actual or planned long-term data archive location:

(Specify NCEI-MD, NCEI-CO, NCEI-NC, NCEI-MS, World Data Center (WDC) facility, Other, To Be Determined, Unable to Archive, or No Archiving Intended)

8.1.1. If World Data Center or Other, specify:**8.1.2. If To Be Determined, Unable to Archive or No Archiving Intended, explain:****8.2. Data storage facility prior to being sent to an archive facility (if any):**

Office for Coastal Management - Charleston, SC

8.3. Approximate delay between data collection and submission to an archive facility:**8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?**

Discuss data back-up, disaster recovery/contingency planning, and off-site data storage relevant to the data collection

9. Additional Line Office or Staff Office Questions

Line and Staff Offices may extend this template by inserting additional questions in this section.